





Solar Optimizer "ABJA"

Shaktisteller Energy Solutions Pvt. Ltd.

p: +91 755 4291895 m: 9425019265 a: 284, Bharat Nagar, J K Road
Bhopal - 24 w: www.shaktisteller.com e: shaktisteller@yahoo.com

THIS PRESENTATION CONTAINS PROPRIETARY AND CONFIDENTIAL INFORMATION OF SHAKTISTELLER ENERGY SOLUTIONS PVT. LTD. AND SHALL NOT BE USED, DISCLOSED OR REPRODUCED, IN WHOLE OR IN PART, FOR ANY PURPOSE OTHER THAN TO EVALUATE THIS PROPOSAL, WITHOUT THE PRIOR WRITTEN CONSENT OF SHAKTISTELLER ENERGY SOLUTIONS PVT. LTD. TITLE IN AND TO THIS DOCUMENT AND ALL INFORMATION CONTAINED HEREIN REMAINS AT ALL TIMES IN SHAKTISTELLER ENERGY SOLUTIONS PVT. LTD.

On-Grid systems: New tech on the block



Integrates the photovoltaic solar with the existing electricity grid.

Inverter synchronizes the AC output with the existing connection via a PLL.

Different inverter topologies and control available in market.

Inverter can be controlled for scheduling dispatch.

Generate your own power

Reduce your energy reading

Sell excess energy to state electricity board (net-metering scheme)

No sizing required; support entire household



Shakti Steller Energy Solutions Private Limited

System Integration

A grid intertie system requires a full understanding of the system & process before connecting to the grid.

System Integration

Solar PV Panel



Inverters



Protection systems



Net-meter

Interoperability Test Response



Panel – Inverter



Inverter – net meter



SRT system – Grid



Solar grid connect: Challenges to traditional power systems

- Government incentives & exponential demand of electrical energy loads to increase number of solar on-grid system.
- Causes pockets of high penetration.
- Variable & unmanaged source of power.
- Impact on stability reliability & efficiency of P.s. grid.
- No longer a negative load, very significant for planning & operation.
- Make them difficult to manage as increase & reliability is required.
- Unplanned location,
- variable sizes,
- variable capabilities,
- fluctuating response to environmental & power situation



Solar : Challenges to system installers

- Sync. With the grid.
- Anti islanding.
- Technical feasibility.
- Power quality problems (different problems in different areas).
- Lack of interest of the field stall of distribution licensee.
- No service level agreement with the residential, small commercial or low voltage customers.



Why a the SRTPV plant faces such problems?

- DISCOM has a huge area with both active and reactive power requirements.
- SRTPV provides only active power. It might happen, that the amount of active power injected in the DISCOM grid might not fully reflect at its input specified for such large system where DER placement is random, unplaced & unmanaged. Disturbs voltage regulation.
 - Unplanned location,
 - variable sizes,
 - variable capabilities,
 - fluctuating response to environmental & power situation.
- Power Quality problems already persistent in the system.
- Long rural/urban feeders length disturbs voltage regulation.



Our Solution

- Practically, we provide a “OLTC” type solution.
- Just like an On-Load tap changer, our optimizer, regulates the voltage at the solar inverter just enough to keep it in sync with the grid.
- Voltage regulation increases due to the installed solar system itself.
- Over time, the system heals itself and continues at proper voltage.



Solar output optimizer basic model:

ABJA

- A Variac (auto transformer) controlled by a servo motor.
- Commands to the servo motor fed through a comparator circuit.
- High insulation rating to allow higher currents to enter the system.





Pilot solar optimizer connected at 3 kW solar grid connect site at Bhopal.



3 kW solar grid connect site photograph at Bhopal.



3 kVA Solax make inverter running smoothly via the optimizer.

Pilot solar optimizer connected at 3 kW solar grid connect site at Bhopal.

The system was connected through wi-fi module and kept under scrutinization for 2 weeks.

Voltage received from the grid was 247 V RMS. Rated voltage of the inverter (single phase) is 230 V.

System out of sync at site for two weeks prior to optimizer installation. Average output per kW = 0 kWh units.

After, pilot installation system in sync for 2 weeks with 11 units of electrical energy output per day (3.9 units average per kW).



Thank You



Shakti Stellar Energy Solutions Private Limited